



# REPOTEX-DUE With cranked drip edge and 12.5 cm mesh

The **APU base clip-on profile REPO-TEX-DUE** is used in compound heat insulation systems as a termination against metal base rails in trough or T-form.

In this way, any movements between plaster junction and metal profile get compensated. The base clip-on profile DUE forms an exact plaster edge.

The base clip-on profile is clipped onto the existing metal base rail. The profile's cranked contour ensures that water is accurately led away. There is a fabric window reveal bead welded onto the profile. Each bar has a fabric overhang on one side of 10cm in the lengthways direction.

The included plug connectors (Z13) and inner and outer corners (Z18-2) enable the profiles to be joined and fitted very precisely.

What is created after completion of the plastering work is a clean termination of the plaster.

# Design

	ITEM NO.	LENGTH	PACKAGING UNIT	WEIGHT (per PU)
REPO-TEX-DUE base clip-on profile				
W64 - 2				
With cranked drip edge and 12.5 cm mesh	W64-2-2500	2.5 m	20  bars = 50  m	7.7 kg

### **Features**


	REPO-TEX-DUE BASE CLIP-ON PROFILE
Material	■ Rigid PVC manufactured under DIN 16941
Mesh	<ul> <li>Min. 160 g/m² approved for compound heat insulation systems</li> <li>12.5 cm wide – MW 4x4mm</li> <li>Ultrasonic welded</li> </ul>
Accessories	<ul> <li>Z13-0000 Plug connectors (1 bag)</li> <li>Z18-2-1010i Internal corners (2 pieces)</li> <li>Z18-2-1010a External corners (4 pieces)</li> </ul>

# Important information


Other applications	Any applications not clearly described in the documents may be implemented only after
	consultation with the plaster or ETICS manufacturer.

For information on materials, areas of use, tests and correct application, please refer to our 'General Advice and Information'

## Details



Sectional drawing in mm



Application drawing