



Window reveal bead with mesh MINI-plus With 12.5 cm mesh

The **APU window reveal bead with mesh MINI-plus** is used in external thermal insulation composite systems (ETICS) in accordance with the APU application range. Within the reveal the profile is stuck flush to the structural element there and thus forms a clean and reliable termination of the plaster with sealing lip.

The profile comes with a self-adhesive PE foam tape, which ensures a watertight, lasting seal. A TPE sealing lip protects the PE foam tape and forms a visually clean joint with the adjacent building component. A fabric strip is welded to the profile. Each bar has a fabric overhang on one side of 10 cm in the lengthways direction There is a piece of self-adhesive tape on protective flap in order to secure the third-party protective film. This protects the window during the plastering work. After completion of these tasks, the protective flap is pulled off and what is created is a clean edge to the plaster.



Area of application

WINDOW POSITION	WITHIN MASONRY		FLUSH WITH MASONRY	IN FRONT OF MASONRY
Sub-surface	With adhesive connection – only for surfaces suitable for being stuck to ! Test of adhesion required			
Insulating material thickness	up to 160 mm			
Window size	up to 2.6 m²			
W21 MINI-PLUS	•		-	-

Can be used only on white plastic windows.

Design

	ITEM NO.	LENGTH	PACKAGING UNIT	WEIGHT (per PU)		
Window reveal head with mesh MINI-nlus						

W21-plus

With sealing lip and 12.5 cm mesh W21-24PLUS 2,4 m 25 bars = 60 m 6,7 kg

Features

	WINDOW REVEAL BEAD WITH MESH MINI-PLUS
Material	 Rigid PVC, manufactured in accordance with DIN 16941 TPE, manufactured in accordance with DIN 16941
Protective flap	Removable flap with soft TPE joint and double-sided adhesive tape
Seal	■ PE foam tape 8x3mm
Mesh	 Min. 160 g/m², approved for use in ETICS 12.5 cm wide, mesh size 4x4mm ultrasonically welded

Important information

Storage	Always store profiles laid down in a dry place.
Use	Can be used only on white plastic windows.
Other applications	Any applications not clearly described in the documents may be implemented only after consultation with the plaster or ETICS manufacturer.

For information on materials, areas of use, tests and correct application, please refer to our 'General Advice and Information'



Details

